

# SUBLIFLOK<sup>TM</sup> - Ref. 1602

#### THE VELVET TOUCH PRINTABLE MEDIA FOR SUBLIMATION PRINTING

Looking for a sublimation media with a special touch personalisation? Subliflok is a smooth touch sublimation printable media developed specially to be printed directly with sublimation inks only.

#### **Fashion Accessories**



#### **Home Decor**



### **Product description**

- ✓ Specially developed to absorb sublimation inks directly from the impression.
- ✓ Smooth velvet touch.
- ✓ Suede-like finish.
- ✓ Very resistant to washing at high temperatures.

# Application key points

- ✓ Perfect for medium designs such as names and number.
- ✓ Printed directly on the product → no need of sublimation paper to transfer the inks.
- $\checkmark$  No tape required  $\rightarrow$  saves production time.

## Usage benefits

 $\checkmark$  Recommended for home decor and fashion accessories.





#### **SPECIFICATIONS**

Composition	Carrier	Dimensions	Inks compatibility
Fibers	Paper support	Available in 50 cm x 10 m	Sublimation

#### **APPLICATION INSTRUCTIONS**

Applies on	Cutting	Application Temp. &  Duration
Cotton Polyester Acrylic & similar fibres	Flock Blade of 60°	170°C – 50 s 338°F – 50 s

#### Recommended tape

No tape

#### Step 1 - Print & Cut:

Program the printing and cutting of the design without rotating the image. Define the cut marks.

#### Step 2- Application on textile:

Remove the backing carrier, place your design on the textile and protect it with a silicone paper. Press it with a Sefa DUPLEX/ROTEX or equivalent at 170°C/338°F during 50 seconds.

#### For sensitive garments:

 $1^{st}$ - Heat press the logo at 170° /338°F during 50 seconds with the backing carrier

2<sup>nd</sup>- Remove the backing carrier and heat press again the logo, on the garment this time at 160°C /320°F during 20 seconds.

NOTE: We highly recommend you to perform tests before launching a production.

# CARE AND MAINTENANCE RECOMMENDATIONS

Washing		Ironing	Tumble- dry	Dry cleaning	
Up to 60°C/140°F Inside out		On reverse side only	Not recomme n-ded	Not recommen- ded	
Storage life	Storage Temperature		Storage Lighting	Position	
Up to 1 year	15°C	oom with C-30°C/ F-86°F	Away from sunlight	Vertical position	

#### **Care and maintenance:**

- ✓ Respect the garments' instructions.
- ✓ Follow the instructions provided by the printer manufacturer.
- ✓ It is important to always use official inks from the printer manufacturer.
- ✓ Printable media are very sensitive: always handle with care and preferably with gloves.
- ✓ Wait 24 hours before the first wash.
- ✓ Avoid the use of aggressive products.

#### Washing recommandations:

- ✓ Preferably inside out to extend design life.
- ✓ Do not bleach.