

Product Sheet

Mod.R&S.05 | Rev.4 | Update 11/2017



TS-MONO

Description

TS-MONO is an automatic heat transfer press providing a pneumatic function and a single supporting plate, characterised by a high productivity.

After transferring, the machine opens automatically swivelling to the side. Operating safety is always ensured thanks to the buttons 'Start' and 'Emergency - Stop'.

Due to its variable printing area and its flexible equipment, TS MONO is suitable for all kinds of applications using heat transfer technology (it is possible to personalize objects up to a thickness of 50 mm).

Optional Plates

Plates for caps

Logo platens 15x15 cm

15x38 cm

Technical Data

 $\begin{array}{lll} \text{Transfer area} & 40 \text{ x } 50 \text{ cm} \\ \text{Heating energy} & 2000 \text{ W} \\ \text{Temperature} & 0-250 ^{\circ}\text{C} \\ \text{Timer} & 0-999 \text{ sec} \end{array}$

Contact pressure $1,2-1,5 \text{ Kg/cm}^2 (2,5-10 \text{ bar})$ Voltage 220 V - 50 hz single-phase

Weight ca. 75 kg





The TS-MONO machine, as it is equipped with electrical parts operating at a voltage between 50 V and 1000 V, is subject to the Low Voltage Directive 2014/35/UE (formerly 2006/95/CE) and the Electromagnetic Compatibility Directive 2004/108/CEE.

The design and construction of the TS-MONO has been made in compliance with the essential safety requisites foreseen by Directive 2006/42/CE.

