

EZ-COLOR™

CUT LETTERING
SIGN VINYL



Premium calendared sign vinyl available in a wide variety of colors that cuts and weeds easily and is ideal for banner graphics, decals, and cut lettering applications.

EZ-Color™

Excellent dimensional stability

Cuts and weeds easily

Available in a variety of colors/patterns and standard roll sizes

For ease of installation, apply cut letters with RTape® Conform® 4075RLA

Soft in nature, adaptable for conforming to curves or flat surfaces

3 mil gloss vinyl facestock rated for <6 years of outdoor durability

Moderate peel, moderate tack permanent adhesive

78# paper liner

Specifically formulated for banner graphics and lettering

Print Compatibility: Thermal

Applications

Banner Graphics

Cut Lettering

Decals

Holiday Décor

Point-of-Purchase

Signage

Bumper Stickers

Fleet Markings

Safety Signage

Commercial Signage

Identification Markings

Appliance Labels

Nameplates



TECHNICAL DATA ▶

Physical Properties		CV300
Finish		Gloss
Color		Various - See Chart
Adhesive		Permanent - P22
Film		Premium Calendered Vinyl
Liner		78#
Opacity		92% minimum
Gloss Level		CD > 70%
Thickness	Film	3.0 ± 0.2 mil
	Film + Adhesive	4.0 ± 0.2 mil
	Total Thickness	8.5 ± 0.2 mil
Adhesion*	SS 15 min room temp dwell	50 oz/in minimum
	SS 24-hr room temp dwell	70 oz/in minimum
Weight	Film + Adhesive	110-125 gsm
	Total w/ Liner	230-250 gsm
Printability		Thermal

Conditions for Use		CV300
Shelf Life*		1 year
Outdoor Durability**		Up to 6 years
Min Application Temp		40 °F (4 °C)
Service Temp Range		-50° to 150°F (-46° to 66°C)
Solvent Resistance***		Good
Water Resistance		Excellent

Store open rolls horizontally, suspended through the core with suitable bar. Do not store vertically on end; this will cause cracking of the sheeting light source.

*When stored at 75° F and 50% relative humidity

**Mid-continental U.S. vertical

***Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.