

Product Bulletin

GF 110

Commercial Grade Dry Erase Film

Permanent Adhesive

GF 110 EraseMark Pro™ is a 50mic clear polyester laminate with a high performance hard coated engineered surface. The scratch and abrasion resistant polyester film is coated with a permanent solvent acrylic pressure sensitive adhesive on a smooth paper liner. This film works well with quality dry erase markers and its anti-graffiti properties allows for easy removal of permanent markers and crayons. GF 110 EraseMark Pro™ has a 5 year interior durability with proper care and cleaning.

Applications

This product is recommended for producing high quality long term dry erase boards typically found in hospitals, retail establishments, restaurants and schools. GF 110 EraseMark Pro™ is a great alternative to replacing whiteboards due to its ease clean, anti-ghosting and yellowing properties. Combine with WallMark™ 226 – 150mic matte white and makes virtually any surface into a dry erase board. Typical substrates are printed photo papers, printed vinyl's and unprinted substrates. This product is also resistance to permanent or semi-permanent markers and crayons, and can be cleaned with rubbing or isopropyl alcohol. For best results, we suggest the following dry erase brand marking pens: Expo Scents® (chisel point), Expo Bold color® (chisel Point), Expo regular® (chisel point) brand marking pens. It is recommended to use a microfiber cloth to clean the films surface. Do not use any chalkboard or felt erasers as this may damage the surface long term. Clean with soapy water and dry with soft microfiber cloth. Ensure no soapy residue is left. To help keep your laminate surface clean and ghost free, we recommend using Remooble™ whiteboard renew. It safely cleans white board surfaces and tough stains. Get more info at www.remooble.com.

Thickness

Film	50mic
Adhesive	25mic
Liner	80gsm
(Thickness variance +/- 10%)	

Dimensional Stability

Film can react to heat in processing. In laminating process do not use excessive unwind tension or nip roll pressure as curl could result.

Temperature Ranges

Minimum application temperature	+4,4°C
Service temperature is	-40°C to +93°C.

Expected Exterior Life

Limited. Dry Erase Film has limited resistance to UV exposure. Test fully for any extended outdoor use.

Adhesion

To stainless steel	12 N/25mm (FTM01)
--------------------	-------------------

Individual values may vary. Test thoroughly before production.

Water Resistance

Good. Immersion not recommended.

Humidity Resistance

Good.

Storage Stability

1-year shelf life when stored at 70°F and 50% relative humidity.

Product Series

E110-54 1,37m x 50m



General
FORMULATIONS

*Manufacturer of Pressure Sensitive Films, Traffic Graffiti
Floor Advertising Films, Custom Coatings and Printing
Inks.*

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537

Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.