

## Processing Instruction - CYS Colored TPU For matte colors with plain adhesive without air-release channels.

For production-related reasons, the matte CYS colors are temporarily being offered with the same plain adhesive as the glossy CYS colors.

### General Properties

The general properties of CYS matte TPU films—in this specific instance without air-release channels—remain unchanged; consequently, the technical specifications remain fully valid. Please continue to observe the "CYS Colored TPU Processing Instruction." This supplement serves to understand and to provide guidance regarding the temporary use of matte colors featuring a plain adhesive layer without air-release channels.

### Application of matte CYS TPU films with plain adhesive, without adhesive channels. With Mounting Fluid – *Wet Application just like Glossy CYS TPU Film*

The matte CYS TPU films with plain adhesive can be applied "wet", using suitable assembly fluid. Thanks to the option of wet application, it is also possible to work with pre-cut templates. This allows for effective material savings.

At <https://cys-europe.de/schneidesoftware-ppf> we recommend independent template software.

**Assembly fluid:** The recommended mixing ratio (can be adjusted depending on temperature and working conditions) of the assembly fluid is "1 liter of water + 3 ml of Film-On".

### With Detailer – *dry for experienced wrappers only*

**Theoretically, the matte, colored CYS films can also be applied "dry":** To reduce the initial tack of the films (matte and glossy), apply a thin layer of SONAX Film Detailer. **Caution:** Keep a distance of at least 3 cm from the edges. (Edges have to clean with Isopropanol).

**However, this application method is recommended only for installers who have already learned wrapping without air-release channels.**

