# productinformation

## tesa® Professional 4024 Universal carton sealing tape

tesa® 4024 is a universal carton sealing tape that comprises a substrate of PP film coated with a special adhesive mass of acrylate (HiTack). The solvent-free sealing tape is especially known for its particularly high adhesive strength, which allows packages to be sealed securely immediately after application. Furthermore, the carton sealing tape can be handled easily by all tesa® manual dispensers, allowing it to be unrolled with very little noise. Due to its high level of resistance to UV light, ageing and temperatures, the adhesive tape offers an extended service life.

### Main Application

- Packaging and closing
- Sealing of light and medium-range weight cartons

#### Technical Data

Backing material	PP film	Adhesion to steel	3 N/cm
Total thickness	50 μm	Elongation at break	140 %
Type of adhesive	acrylic	Tensile strength	45 N/cm

### **Properties**

•	Automatic application	yes	•	Printability	•••
•	Manual application	yes	•	Low noise unwinding	yes

Evaluation across relevant tesa® assortment: ••• very good •• good • medium • lov

## productinformation

### tesa® Professional 4024 Universal carton sealing tape

tesa® 4024 is a universal carton sealing tape that comprises a substrate of PP film coated with a special adhesive mass of acrylate (HiTack). The solvent-free sealing tape is especially known for its particularly high adhesive strength, which allows packages to be sealed securely immediately after application. Furthermore, the carton sealing tape can be handled easily by all tesa® manual dispensers, allowing it to be unrolled with very little noise. Due to its high level of resistance to UV light, ageing and temperatures, the adhesive tape offers an extended service life.

### Main Application

- Packaging and closing
- Sealing of light and medium-range weight cartons

### Technical Data

Backing material	PP film	Adhesion to steel	3 N/cm
Total thickness	50 μm	Elongation at break	140 %
Type of adhesive	acrylic	Tensile strength	45 N/cm

### **Properties**

•	Automatic application	yes	•	Printability	•••
•	Manual application	yes	•	Low noise unwinding	yes

Evaluation across relevant tesa® assortment: ••• very good •• good •• medium • low