

SOLVENT číslo artiklu: SBQ-SBM340R.. SOLVENT BLOCKOUT BANNER MATTE 340

Double layer coating with PET&PP provides anti-curling and proper stiffness. The matte finish reduces glare, and improve density. Non transmissive backside coating is the perfect background for brilliant full color prints. Very good rolling properties and flatness, creat brilliant color reproduction. Tear and fade resistant, the material will withstand all types of weather conditions.

APPLICATION

X, Y banner stand
Window shades, stand displays, shop and exhibition works
Point of sales, posters
POP-UP Banner

SPECIFICATION

Caliper	340 micron (13.6mil)
weight	415g
Base material	PET&PP
Surface	Semi-matte
Width	36", 50", 60"
Length	20m (65 ft)
Core	3"

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility

ECO



Solvent



UV-

Curable

Printer Compatibility

Most Solvent & Eco Solvent Printing system: LATEX & HP, Epson, Roland, Mimaki, Mutoh, Seiko, Oce

TECHNICAL DATA

Caliper	340micron	ASTM D645
Gloss	10/15	ASTM D2457
L.a.b	85/ 0 / -5.0	ANSI T
		D50/2°/Abs/No

GUIDELINES

Printing Tip

Dry time will vary depending on ink type.
It is necessary to dry up and not to overlap the printed material.

Lamination:

Lamination is optional. In order to protect the image from physical damage, overlaminates is recommended.

Storage:

It is recommended to store in the closed original packing in a cool and dry environment
Temperature 10°~30°C (50°~86°F), Humidity 35~65% RH

Shelf Life:

One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.