

PRICE LIST EURO

ROLL-X

ROLL-X[®] ADVANTAGE

ROLL-X ADVANTAGE gives you access to the superior production method provided by the Flatbed Applicator technique. The machine can either be shipped in modules to reduce shipping cost and gives you the possibility to fit through a standard door, or be delivered fully assembled. The assembling is fast and easy and you will start making money in no time! Possible to retrofit LED and Electrical height adjustable legs.

MODEL	327/175	400/175	470/175
Model type	Advantage	Advantage	Advantage
Part no.	10529	10532	10533
Bed length	3 270 mm / 10ft. 9in.	4 000 mm / 13ft. 1in.	4 700 mm / 15ft. 5in.
Bed width	1 750 mm / 5ft. 9in.	1 750 mm / 5ft. 9in.	1 750 mm / 5ft. 9in.
Length of working area	2 870 mm / 9ft. 5in.	3 600 mm / 11ft. 10in.	4 300 mm / 14ft. 1in.
Width of working area/roller width	1 650 mm / 5ft. 5in.	1 650 mm / 5ft. 5in.	1 650 mm / 5ft. 5in.
Work height flatbed	850-1 070mm / 2ft. 9in - 3ft. 6in.	850-1 070mm / 2ft. 9in - 3ft. 6in.	850-1 070mm / 2ft. 9in - 3ft. 6in.
Max. thickness of substrate	85 mm / 3 2/5in.	85 mm / 3 2/5in.	85 mm / 3 2/5in.
Bed surface	tempered glass + cutting mat	tempered glass + cutting mat	tempered glass + cutting mat
Height-adjustable table	manual	manual	manual
LED (light)	option	option	option
Roll holder, glide beam	yes	yes	yes
Roll holder, short side	yes	yes	yes
Casters	yes	yes	yes
Warranty	2 years	2 years	2 years
Price	11 900 €	12 900 €	13 900 €

OPTIONS TO IMPROVE YOUR ROLL-X[®]

PRODUCT			
LED	500 €	500 €	500 €
Electrical height adjustment	2 000 €	2 000 €	2 000 €
Roll cradle 1 300 mm / 4ft. 3in.	165 €	165 €	165 €
Assembled when delivered*	1 000 €	1 000 €	1 000 €

* Ex Factory

ROLL-X[®] PRO

ROLL-X PRO is the fully equipped multipurpose work table that gives you access to the superior production method provided by the Flatbed Applicator technique. The machine can either be shipped in modules to reduce shipping cost and gives you the possibility to fit through a standard door, or be delivered fully assembled. The assembling is fast and easy and you will start making money in no time! ROLL-X Pro is equipped LED and electrical height adjustment.

MODEL	327/175	400/175	470/175
Model type	Professional	Professional	Professional
Part no.	10534	10535	10536
Bed length	3 270 mm / 10ft. 9in.	4 000 mm / 13ft. 1in.	4 700 mm / 15ft. 5in.
Bed width	1 750 mm / 5ft. 9in.	1 750 mm / 5ft. 9in.	1 750 mm / 5ft. 9in.
Length of working area	2 870 mm / 9ft. 5in.	3 600 mm / 11ft. 10in.	4 300 mm / 14ft. 1in.
Width of working area/roller width	1 650 mm / 5ft. 5in.	1 650 mm / 5ft. 5in.	1 650 mm / 5ft. 5in.
Work height flatbed	850-1 070mm / 2ft. 9in - 3ft. 6in.	850-1 070mm / 2ft. 9in - 3ft. 6in.	850-1 070mm / 2ft. 9in - 3ft. 6in.
Max. thickness of substrate	85 mm / 3 2/5in.	85 mm / 3 2/5in.	85 mm / 3 2/5in.
Bed surface	tempered glass + cutting mat	tempered glass + cutting mat	tempered glass + cutting mat
Height-adjustable table	electrical	electrical	electrical
LED (light)	yes	yes	yes
Roll holder, glide beam	yes	yes	yes
Roll holder, short side	yes	yes	yes
Casters	yes	yes	yes
Warranty	2 years	2 years	2 years
Price	13 900 €	14 900 €	15 900 €

OPTIONS TO IMPROVE YOUR ROLL-X[®]

PRODUCT			
LED	included	included	included
Electrical height adjustment	included	included	included
Roll cradle 1 300 mm / 4ft. 3in.	included	included	included
Assembled when delivered*	1 000 €	1 000 €	1 000 €

* Ex Factory

SELECTED PRODUCTS

ROLL-X SELECTED PRODUCTS will make your daily sign production easier and more efficient. Based on many years of experience from the sign industry they are developed and selected to meet the future. They will soon be available at your nearest ROLL-X dealer.



WILL SOON BE AVAILABLE

APPLICATION AREAS

MOUNTING

ONE OPERATOR CAN MOUNT LARGE FORMAT

digital print and self-adhesive film to many substrates like acrylic, rigid boards, corrugated plastic, metal plate, banners and glass. The flatbed gives you complete control over positioning and produces a result free from bubbles and creases.

PRE-MASKING

IT ENABLES A SINGLE PERSON TO APPLY

transfer tape to cut vinyl graphics from the built in tape roll holder.

LAMINATION

DESIGNED FOR COLD FLATBED LAMINATION

of digital prints and signs, by using pressure sensitive lamination film direct from roll or sheet by sheet for minimum waste.


WORK TABLE

YOU NEED NO FURTHER CUTTING TABLE

ROLL-X will become your new work table with a unique self-healing cutting mat, metal side lines used for trimming, height adjustable legs and adjustable/removable side trays.

INCREASE YOUR PROFITS

- No re-makes
- Consistent high quality
- Great time savings
- Ergonomic and easy to use, does not require specialized operator.



CALCULATE YOUR ROI

WANT TO SEE HOW MUCH TIME AND MONEY YOU CAN SAVE?

The ROLL-X ROI Calculator easily calculates how much you earn on replacing your traditional approach to the unique ROLL-X Flatbed Applicator method.

Can you afford not to?
Please visit roll-x.se for more information and to calculate your profit.

roll-x.se/calculator

ROLL-X BY ROLLSROLLER

ROLL-X

Multipurpose applicator

FREE ACCESS TO THE ROLLER

METAL SIDE LINES
FOR TRIMMING

ROLL HOLDER SHORT SIDE AND GLIDE BEAM

ADJUSTABLE/REMOVABLE SIDE TRAYS

ELECTRICAL OR MANUAL HEIGHT ADJUSTABLE TABLE

ROLL-X IS A MONEY MAKER

WANT TO SEE HOW MUCH TIME AND MONEY YOU CAN SAVE?

While getting access to a technology that will revolutionize your entire work process? The ROLL-X ROI Calculator easily calculates how much you earn on replacing your traditional approach to the unique ROLL-X Flatbed Applicator method. How much foil and premask do you use? How much time do you spend per application? What is the total labour cost? Fill in your values and discover how fast your return on investment will be.

THE QUESTION IS CAN YOU AFFORD NOT TO?



roll-x.se/calculator



ROI Calculator



**FAST ASSEMBLY
AND INSTALATION**

ROLL-X® ACCESSORIES

IT'S EASY TO UPGRADE YOUR ROLL-X

Great accessories to improve and modify your ROLL-X Flatbed Applicator. To make your job even easier, choose between many original accessories to improve your daily work.



Roll-X long life compressor (45 db)

Stop static kit, cord and magnet

Self healing cutting mat

PRODUCT NAME	DESCRIPTION/DIMENSIONS	PRICE
Roll-X long life compressor	Voltage 230V/50Hz / 120V/60Hz	790 €
Stop static kit	Used to reduce static electricity. Includes 1 m cord and 1 magnet	40 €
Long reach cutter 60	Length 600 mm / 1ft 1in. Extra titan blades 10pcs are included.	64 €
Long reach cutter 90	Length 900 mm / 2ft 2in. Extra titan blades 10pcs are included	74 €
SELF-HEALING CUTTING MATS	DESCRIPTION/DIMENSIONS	PRICE
Cutting mat 327/175	3270 x 1680 mm / 9ft. 2in. x 4ft. 9in.	On request
Cutting mat 400/175	4000 x 1680 mm / 13ft. 1in. x 4ft. 9in.	On request
Cutting mat 470/175	4700 x 1680 mm / 15ft. 5in. x 4ft. 9in	On request

GENERAL INFORMATION

REQUIREMENTS:

ROLL-X Multipurpose Applicator® requires air supply of 2,5 bar / 36 psi / 0,25 MPa pressure, 230 volt/50 Hz electrical supply (available as US model 120 volt/60Hz)

DELIVERY

Roll-X is delivered in parts as standard. Assembled from factory is optional.

ASSEMBLY

If delivered in parts: follow the ROLL-X installation manual included in the package.

If delivered fully assembled: lift the machine off the pallet, connect it to a power supply and follow instructions in the Owner's manual.

WARRANTY:

2 years warranty, excluding glass and electrical parts. Visit our website www.roll-x.se and download complete conditions.

OFFLOADING INSTRUCTIONS:

ROLL-X requires a forklift.

If delivered in parts: Crate is 580 mm wide (normal length is enough).

If delivered fully assembled: Crate is 2000 mm wide and we here recommend forks at least 1 700 mm long and sufficient capacity to lift the full weight of the ROLL-X model.

Lift the ROLL-X under the steel frame within areas marked "forklift ↓".

ANY QUESTIONS?

Contact Induflex AB if there are any hesitations or questions!

+46 54 770 70 30
info@roll-x.se



ROLL-X

ROLL-X
Induflex AB
Frögatan 3
SE 653 43 Karlstad, SWEDEN
Phone: +46 54 770 70 30
E-mail: info@roll-x.se
E-mail: order@roll-x.se
Web: www.roll-x.se

**Patented product
developed and manufactured
by Induflex AB in Sweden**

CE