

WINDOW CLING PRODUCT SERIES

SO820ST-

Číslo artiklu: SFQ-SSACR137-30-AK

SOLVENT SILICON -CLING CLEAR FILM

1. Automatical wetting on the certain window
2. Perfect Transperant
3. Nobody produce : Solvent-Based Hi-Glossy Coating + Silicone-Adhesive

NaturaMedia is introducing and launching Window Cling Film series as of 2012 y'. This film is one of top high quality products among Natura Window Cling films, especially 'SILICONE' materials. This base film is ultra clear transparent Polyester with removable for indoor window decoration. This SILICONE material is easy to stick on and easy to remove. It can be used correct as many times as you need. Not using glue, so there is no sticky feeling and does not leave any glue on the surface.

* Cautions

- Before printing, handle this film with gloves to avoid marks during printing.
- Not suitable for unflatness surface
- Not recommended for outdoor usage
- Clean the mounting object before applying SO810ST

APPLICATION

Window Decoration

ROAD SHOP Window Advertisement

Fashion, Sports, Electronics, Veichle, Deli, Coffee, Etc

INDOOR Window Advertisement

Conference rooms, Lobbies, Retail identification signs

Residential interiors, Office Privacy, Glass partitions and cubicles

SPECIFICATION

Caliper	150 micron (6.0 mil)
weight	185g/m ²
Surface	ULTRA Transparent (Clear)
Base Material	Clear Polyester
Width	50"
Length	30m (100 ft)
Core	3"

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility

Solvent-Based / Latex / UV-Curable

TECHNICAL DATA

Caliper	175 micron	ASTM D645
Gloss	Transparent	ASTM D2457
L.a.b	Transparent	ANSI T (D50/2 ^θ /Abs/No)

GUIDELINES

Printing Tip Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%
Use care in handling printed material, surface susceptible to abrasion
To optimize the printing quality, printer need to be set for hightest print quality.

Lamination: Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminat is recommended.

Storage: It is recommended to store in the closed original packing in a cool and dry environment
Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH

Shelf Life: One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affact results.

Application

ROAD SHOP Window Advertisement

Fashion Full Color
Wall cover
Reverse
Inside



Sports & Coffee Full Color
Wall cover
Reverse
Inside



Furniture Full Color
Etched
Reverse
Inside



INDOOR Window APPLICATION

Conference room & POS Full Color
Reverse
Inside

